

50

FLEXIBLE MOUNTING SUBSTRATE

Patent Number: JP63249345
 Publication date: 1988-10-17
 Inventor(s): YAMAMOTO HIDEO
 Applicant(s): OLYMPUS OPTICAL CO LTD
 Requested Patent: ☐ JP63249345
 Application Number: JP19870083066 19870406
 Priority Number(s):
 IPC Classification: H01L21/60; H05K1/18
 EC Classification:
 Equivalents:

Abstract

PURPOSE: To enable an ultrasonic wire bonding requiring no bump formation by providing, in the substrate portion corresponding to the end portion of a lead formed on the rear of a soft substrate, an opening for wire connection having a width smaller than the lead width, thereby constructing a flexible mounting substrate.
CONSTITUTION: In the substrate 1 portion corresponding to the end portion of a lead 2 which was formed for connection of an electronic component such as a semiconductor IC chip 5 by patterning a conductive layer on the substrate 1 surface, an opening 3 for wire connection is formed which has a width smaller than that of this lead. With this, a ultrasonic wire bonding requiring no bump is enabled through the opening 3 for wire connection. Also, since no opening passing through to the surface and rear of the substrate 1 is formed, the resin encapsulation can be provided only at the side on which the electronic component such as the semiconductor IC chip 5 is mounted, thereby enabling a thin- type packaging.

Data supplied from the esp@cenet database - I2

BEST AVAILABLE COPY